

# MULTI-TANK TRAILERS



# NO CDL. NO HAZMAT. NO PROBLEM.

The Multi-Tank Trailer from Thunder Creek is the first fuel and service trailer to legally mitigate the need for the driver to have a HAZMAT endorsement.\* In many cases, a CDL is also not required.

The trailers can be configured with four, six or eight non-spec, 115 gallon fuel tanks. Each tank stands alone as a DOT compliant, non-bulk, diesel fuel tank capable of being transported without a HAZMAT. Tanks are joined via a manifold to a common pump allowing for complete isolation during transport as well as controlled dispensing of fuel at the job site. A new electric valve manifold option automatically closes the manifold to ensure DOT Compliance without operator intervention.

These trailers can now be equipped with a new gas powered pump option, as well as the popular rear utility box and 100 gallon DEF system. This patent-pending closed DEF system is fully ISO-compliant to maintain DEF purity and protect Tier 4 equipment.

\*Per the Code of Federal Regulations, Title 49 (CFR49). The Multi-Tank Trailer specifically uses independent non-bulk packaging for the transportation of combustible liquids in the U.S. Contact us for details about state regulations.

LEGALLY TRANSPORT BULK DIESEL WITHOUT A HAZMAT



#### FUEL | DEF | SERVICE | LUBE



## **MULTI-TANK TRAILERS** LEGALLY TRANSPORT DIESEL FUEL WITHOUT A HAZMAT\*

#### INDUSTRY LEADING 3 YEAR TANK WARRANTY



### STANDARD FEATURES

#### **TRAILER FEATURES**

- Dual Coat Polyurethane Paint
- Diamond Plate Rock Guard on Fenders & Frame
- Replaceable Bolt-on Fenders
- Lockable Hatch-Style, Weather-Sealed Doors
- Dexter® Torsion Axles and EZ Lube Hubs
- Self Adjusting Electric Brakes
- Breakaway Safety System
- 16" 10-Ply Tires 235/80R16 with Steel Wheels

#### TANKS AND PUMPING SYSTEM

- 115 Gallons per Tank, up to 8 Tanks
- 7 Gauge Steel Tanks with Sloped Bottoms
- 12V Deep Cycle Battery
- 12' Power Cables
- 35' Retracting Hose Reel
- Auto-Trip Nozzle

- 7,000 lb. Enclosed Jack
- · Safety Tow Chains
- Adjustable Height 2 5/16" Ball Hitch
- Reflective Tape and LED Lights
- · Wiring Wrapped in Protective Braid
- 7.5" x 1/4" Formed Frame
- Automatic Interior LED Lighting
- · Fire Extinguisher
- Extruded Aluminum Pump Manifold
- Spinsecure<sup>™</sup> Locking, Vented Fuel Caps
- · 25 GPM Industrial Grade 12V Pump
- Sight Fuel Level Gauges
- 10 Micron Fuel Filter

#### **OPTIONS**

Items with + can be added any time to expand the functionality of the trailer as your operation grows.

#### **TRAILER OPTIONS**

Aluminum Wheels Field Max Tires Custom Color Solar Battery Maintainer • WorkSight Light Tower • Electric/Hydraulic Jack • Spare Tire Kit with Standard or Field Max Tires • Stainless Steel Trim + Fender Upgrade

#### **PUMPING SYSTEM OPTIONS**

Gas Engine Pump Upgrade Electric Valve Manifold for Automatic Shut-Off 2 Stage Filter System (10+4 Micron) Upgrade • Digital Fuel Meter for Gas or Electric Pumps • Analog Fuel Meter for Gas or Electric Pumps • 50' Fuel Hose Reel Upgrade Static Discharge Reel • Spill Containment Kit •

#### REAR UTILITY BOX OPTIONS

Rear Utility Box (39.5"d x 58.5"w x 49"h) • Five Drawer Tool Chest for Utility Box • Can+Towel Holder • Two Drawer Low Boy Tool Chest • Work Bench with Vise • 35 lb. Grease Kit • Welder+Comp+Gen with 50' Air/Elec. Combo Reel • Comp+Gen with 50' Air/Elec. Combo Reel • 35 CFM Air Compressor with 50' Air Hose Reel •

#### DIESEL EXHAUST FLUID OPTIONS

100 Gallon DEF Tank, Pump and 35' Reel + Digital DEF Meter + 50' DEF Hose Reel Upgrade 110V DEF Heater +

SPECIFICATIO	NS		
Model	МТТ460	мтт690	МТТ920
115 Gallon Tanks	4 tanks   460 gal. total   7 gauge	6 tanks   690 gal. total   7 gauge	8 tanks   920 gal. total   7 gauge
Torsion Axles Hubs	dual 5,000 lbs. axles   6 bolt hubs	dual 6,000 lbs. axles   8 bolt hubs	dual 7,000 lbs. axles   8 bolt hubs
L   W   H*	13'   7'   6'	16'   7'   6'	18'   7'   6'
Empty Weight*   GVWR	3,326 lbs.   10,000 lbs.	4,054 lbs.   12,000 lbs.	4,682 lbs.   14,000 lbs.

\*A rear utility box adds 3'4" to the length and 650 lbs. to the empty weight.